



DN	ØD	ØD1	n-Ød	α°	H	H1	H2	L	L1	ØD2	N-Ø	b'	S	F	H3
50	90	50	4-Ø7	45	112	80	32	108	9	125	4-Ø18	45	3	22	13
65	90	50	4-Ø7	45	136	85	32	112	11	145	4-Ø18	45	3	22	13
80	90	70	4-Ø9	45	145	98	32	114	14	160	8-Ø18	22.5	3	22	13
100	90	70	4-Ø9	45	155	114	32	127	14	180	8-Ø18	22.5	3	23	15
125	90	70	4-Ø9	45	172	127	32	140	14	210	8-Ø18	22.5	3	24.5	15
150	90	70	4-Ø9	45	182	138	32	140	17	240	8-Ø22	22.5	3	26	15
200	125	102	4-Ø11	45	201	175	40	152	17	295	12-Ø22	15	3	29	17
250	150	125	4-Ø14	45	242	204	40	165	22	355	12-Ø26	15	3	32	17
300	150	125	4-Ø14	45	277	237	45	178	22	410	12-Ø26	15	4	36	22
350	175	140	4-Ø17.5	45	315	260	45	190	27	470	16-Ø26	11.25	4	39	25

7	BODY	GGG40.3	1	
6	DISC	C954	1	
5	PIN	Duplex	(DN50-125 1PCS) (DN150-350 2PCS)	
4	SEAT	EPDM/NBR	1	
3	BUSHING	Brass	4	
2	"O" RING	NBR	1	
1	STEM	SS431	1	
NO.	PARTS NAME	MATERIAL	QTY	

TEST PRESSURE	HYDROSTATIC	SHELL	SEAL
	AIR	1.5 MPa	1.1 MPa

STANDARD	DESIGN CODE	API609
	INSPECTION TEST	API598
	END STANDARD	DIN EN 1092-2 PN16
	FACE TO FACE	ISO 5752-Series 13

Double flange BUTTERFLY VALVE DN50-DN350			
APPROVED			REV
CHECKED			
DRAWN			UNIT
DESIGNED			MM
SIGNATURE			

出(地)用件登记

插图

描校

旧底图总号

底图总号

签字

日期